






# IMAGO Muses Omni-Directional Microphone Array





The MUSES delivers true omnidirectional performance ideal for a vast range of conference room/smart classroom settings.



## Speaker ability

Speakerphone with the ability to steer the directionality of the device's microphones. This feature works in conjunction with direction finding.

#### Noise cancellation

Beamforming improves noise and echo cancelling, howling suppression, dynamic noise suppression as well as the overall quality of the device's pickup.






# Omnidirectional microphone

Omnidirectional microphone with the ability to recognize the direction of the person speaking in the room. Equipped with 12V 1A fast charge.

### Built in 5G wireless speakerphone

Built-in 2 x 5W speakerphone via 2.4 Ghz / 5 Ghz wireless or USB 2.0 connection.





#### Flexible relocation

Small size for easy relocation, USB Plug & Play. The LED's indicate the voice pick up & direction as well as muting. Wall Mountable.

# **SPECIFICATIONS**

Conference Speakerphone with expansion Microphones				
Built-in Audio				
Built-in Digital silicon Microphone	Туре	Digital silicon Microphone		
	Sensitivity	Built-in Microphone : -22dBFS		
	SNR	60dB		
	Frequency response	100Hz - 16kHz		
Echo Cancellation		world-class Echo cancellation technology, echo cancellation time up to 256ms		
Noise Cancellation		>12dB		
Sampling frequency		Record: 16kHz / Playback: 48kHz		
Voice pick up range		3M		
Transmission Model		Wired, USB2.0 (Between all-in-one device and PC) Wireless, 2.4Ghz / 5Ghz (Between all-in-one device and Microphone)		
Speaker power		Double Channels 4Wx 2		
All-in-one Device Power		9W MAX		
Control Mode		Touch button control / remote control		
Button function		ON/OFF (Baterry Check), Volume+, Volume-, speaker mute, microphone mute, scene switch		
Remote function		Audio: Volume+, Volume-, microphone mute, speaker Mute, ON/OFF  Video: ZOOM+, ZOOM-, up/down/left/right movement, OSD Menu		
Status Display		Two-color LED indicator		
Power adapter		DC12V±0.2V,1A		
Working tempreture		-10 C °∼ 40 C		
Enviroment humidity		0-95% RH		
Weight		950g		

Wireless Microphone (Comes with 3 expansion Microphones)			
Туре	Digital Silicon Microphone		
Sensitivity	-26dBFS @ 1kHz 1Pa		
SN	59dB		
Frequency Response	100Hz - 16kHz		
Sampling Frequency	Record: 48kHz		
Voice pick up range	3M		
Wireless Transmission Model	2.4Ghz / 5Ghz		
Wireless Transmit Power	2.4G: 5dBm		
Microphone Power	0.2W MAX		
Charge Jack	USB type-C / Charging board contact charging		
Control Mode	Touch button control		
Button Function	On/OFF, Microphone Mute		
Status Display	Two-color LED indicator		
Power Adapter	Charging board DC5V+0.2V, 2A		
Battery	800MAH		
Standby Time	6 month		
Work Time	>8 hours		
Working Temperature	-10 -40°C		
Enviroment Humidity	0-95% RH		
Length*Weight*Height	70x49mm		
Weight	300g		

Name	Charging Board
Input voltage/current	5V/2A
Maximum number of Microphone get charged	2pcs
Single output current	600mA
Dimension	200x100x16 (mm)
Weight	170g
Interface	USB type-C



Collaborate | Inspire | Imagine

#### IMAGO TECHNOLOGIES LLC

2093 Philadelphia Pike #7836 Claymont, DE19703, United States of America.

sales@imago techs.com

Follow us





Authorised Partner