



IMAGO Meeting Pad Superchange Your Meeting Productivity & Team Collaboration



IMago

Applications & Solutions





IMAGO Flash

IMAGO Flash is IMAGO's proprietary video conference application built with rich capabilities and usability that promote consistent performance and user experience across any device and platform. IMAGO Flash is a fully secured, instant collaboration tool to have an effective virtual meeting, which enables a seamless experience of setting up or joining a video call at your fingertips, wherever, whenever with just 1 single application.

Why IMAGO Flash?

FLash

- Instant Virtual Meeting Join or host a virtual meeting in seconds.
- Supports any web browser on any device No additional application or plugin is required for the host or participants.
- Scalability and higher video quality for meeting collaboration with Hybrid private cloud.
- Seamless video sharing.
- Built-in collaborative whiteboard (IMAGO Collab) with co-editing feature.
- Comes with an interactive polling feature & breakout rooms.

IMAGO Smart Present

tools they need to have a seamless presentation experience from a traditional physical meeting. The host can moderate how users engage either in 1:1 mode or team collaboration. The host can also easily manage how users can share their screens and collaborate.

IMAGO Smart Present supports collaboration from any device, making your interaction with any IMAGO all-in-one system easy.

Benefits include:

- Collaborative tools for interactive & fun sharing.
- Share your ideas effortlessly with real-time screen mirroring up to 9 devices.
- 100 devices or more. Sharing is made even easier with high compatibility with multiple OS: Android, iOS, Windows, Mac & Chrome.

IMago

Applications & Solutions







COLLAB

IMAGO Collab

A virtual whiteboard for live collaborations with a

feature-rich library. IMAGO Collab is a lightweight virtual whiteboard that enables distributed teams to work together effectively and seamlessly.

Compatible with any device and browsers.

IMAGO Collab works on any device, from laptops to desktops, tablets, and mobile devices. It is also optimised for all browsers from Chrome to Safari and Edge.

Never too Far to Collaborate.

Collab empowers remote, onsite, and hybrid teams to communicate and collaborate across various formats, tools, channels, and time zones - without the constraints of a physical location, meeting space and whiteboards

Supercharge Your Brainstorming Sessions. IMAGO Collab is equipped with templates and a feature-rich sketching library to facilitate effective brainstorming sessions or team discussions. For example, users can start their brainstorming session quickly and efficiently by simply importing their favourite brainstorming or mind-mapping templates from the library without having to create one from scratch.

WORK

IMAGO Work

A Secured & Reliable File-Sharing & Collaboration Solution.

IMAGO Work is a secured and reliable productivity platform for file sharing that keeps team members in sync by allowing users to collaborate in a real-time manner on documents and project

IMAGO Work is equipped with rich collaboration features that empower remote and distributed teams to share effectively despite the distance.

These features include file preview, file access control, file locking, online editing with remote collaboration, user management and single sign-on, cross-platform file syncing, data backup and recovery.

SPECIFICATIONS

<table-container><table-container></table-container></table-container>	Model	IMB-65-ENT	IMB-75-ENT	IMB-86-ENT	
<table-container><<table><th and="" cols="" of="" set="" t<="" td="" the=""><td>DISPLAY</td><td></td><td></td><td></td></th></table></table-container>	<td>DISPLAY</td> <td></td> <td></td> <td></td>	DISPLAY			
<table-container><<table>NameImageSecond<td< td=""><td>Diagonal Screen Size</td><td>65″</td><td></td><td>86"</td></td<></table></table-container>	Diagonal Screen Size	65″		86"	
<table-container><<table>imageimageimageBigSecondSecond<t< td=""><td>Light Source</td><td></td><td></td><td></td></t<></table></table-container>	Light Source				
<table-container><<table><th and="" cols="" of="" set="" td="" th<="" the=""><td>Brightness</td><td></td><td>590 cd/sq.m.</td><td></td></th></table></table-container>	<td>Brightness</td> <td></td> <td>590 cd/sq.m.</td> <td></td>	Brightness		590 cd/sq.m.	
<table-container><<table>imageimageimageimageImageImageStatum<!--</td--><td>Contrast</td><td></td><td>5000:1</td><td></td></table></table-container>	Contrast		5000:1		
<table-container><<table>linkimage<td>Resolution</td><td colspan="3">3840 x 2160 (4K)</td></table></table-container>	Resolution	3840 x 2160 (4K)			
< <table>SharkanSecond Second S</table>	Response Time		5ms		
<table-container><<table><th and="" cols="" of="" s<="" set="" td="" the=""><td>/iewing Angle</td><td colspan="3">1780</td></th></table></table-container>	<td>/iewing Angle</td> <td colspan="3">1780</td>	/iewing Angle	1780		
<table-container>Water with a strain of the strain of the</table-container>	Display Colour		10 bits		
<table-container>SolutionISignedIISigned<t< td=""><td>Screen Protection</td><td></td><td></td><td></td></t<></table-container>	Screen Protection				
<table-container><<table-container><t<table-row>Main and the set of the</t<table-row></table-container></table-container>	RGB Signal		VGA/ SVGA/XVGA/SXGA/WUXGA		
< <table>Selection of the selection of</table>	CONNECTIVITY (INPUT)				
<table-container><table-container><math><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></math></table-container></table-container>	IDMI Input 2.0		х3		
<table-container><table-container><math><table-row><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-row></math></table-container></table-container>	Display Port		x1		
< <table>34. def contract of the set of th</table>	Audio Input		x1		
<table-container>gainediselectionGigonal GaloSelectionSelectionGigonal GaloSelectionSelection<</table-container>	HDMI Touch		x1		
< <table> dial </table>	JSB C		х2		
<table-container>sequencesisiSequencesi<</table-container>	JSB 2.0		х2		
<table-container>search1SearchI<</table-container>	JSB 3.0		х5		
<table-container>SATEIPheneISectorI<td< td=""><td>thernet LAN (RJ45)</td><td></td><td>x1</td><td></td></td<></table-container>	thernet LAN (RJ45)		x1		
<table-container><th and="" cols="" of="" set="" set<="" td="" the=""><td>oaxial Input</td><td colspan="3">x1</td></th></table-container>	<td>oaxial Input</td> <td colspan="3">x1</td>	oaxial Input	x1		
<table-container>search of the second of the second</table-container>	15232	x1			
<table-container>980404•ishould be should be s</table-container>	IP Touch		x1		
<table-container>ifSetter Setter Set Setter Setter Set Setter Setter Setter Set Setter Set Set Set Set Set Set Set Set Set Set</table-container>	CONNECTIVITY (OUTPUT)				
<table-container>distant set of the set of</table-container>	HDMI Output 2.0		x1		
<table-container>NAMANDESBrank SeriesSeriesBrank SeriesSeriesSeries Series SeriesSeriesSeries Series SeriesSeriesSeries Series SeriesSeriesSeries Series SeriesSeriesSeries Series Series SeriesSeriesSeries Series Series SeriesSeriesSeries Series Series Series SeriesSeriesSeries Series Series Series SeriesSeriesSeries Series Series Series Series SeriesSeries Serie</table-container>	Audio Output (3.5mm)	rt I			
<table-container><th and="" cols="" of="" set="" td="" the="" the<=""><td>Ethernet LAN (RJ45)</td><td colspan="3">hx l</td></th></table-container>	<td>Ethernet LAN (RJ45)</td> <td colspan="3">hx l</td>	Ethernet LAN (RJ45)	hx l		
<table-container>naniaminterfactorBandmin</table-container>	INTERACTIVE PARAMETER				
<table-container>searcherSignationImplication<</table-container>	Touch Surface		Anti-Break		
<table-container>intensionIntensityIntensityisaki balanceIntensityIntensityisaki balanceI</table-container>	Touch Sensor		IR		
<table-container>seletionImportant of the selection of</table-container>	Touch Point				
<table-container>indexItem is the instruction of the instruction of</table-container>	Writing Tool		Pen or Finger		
<table-container>sine defend13 pinot/sbis defend so comparing the set of the se</table-container>	ouch Resolution		32767 x 32767		
<table-container>bindInfideal control</table-container>	Response Time				
<table-container>man factor Singular Singular</table-container>	Cursor Speed		125 point/s		
<table-container></table-container>	Positioning Accuracy		1mm		
<table-container>Baile algobientCarabite LangebasedSecond Second Se</table-container>	Interface to Computer (External)		USB (Touch Out) × 2		
<table-container>Balle MindepandentGeneration of the state of</table-container>	SOUND				
<table-container>CMEAIGeneral Relation Canas ResolutionStagageties Value angleCanase Relation Canase Rel</table-container>	Built-in Speakers		2 x 20 watts , 1 x 20 watts subwoofer		
<table-container>Balika Ganea GaleBiographics, 104 wide angleGamea Balanta</table-container>	Built-in Microphones	6x built-in be	amforming microphones coverage up to 10 meters, supported wide band aud	lio & echo cancellation	
Gamea Realidance PRO [1920/1000] Gamea Realidance International System Control System Contro	CAMERA				
Bive Bir	Built-in Camera	8 Megapixels , 104 wide angle			
<table-container>Provide and the set of th</table-container>	Camera Resolution				
Intersor InterSore is / Core is /	Camera Adjustment		15° Vertical Adjustment		
BMAImage: BGA/16 GBSengeImage: Senge S	OPS Processing (Optional)				
Bangen of the stand o	Processor		Intel Core i5 / Core i7 (11th Gen)		
Abart a interact of the second of the	RAM	8 GB / 16 GB			
MM descriptionAdda & SolizAdda & Soliz	Storage	128 GB / 256 GB SSD			
ANDROID Processing Processor Gene State Stat					
Processor Octa-Core with pair of Quadore AT3 & AS3 (Eah Core 2:86Hz) Graphics Processor Get Octa-Core Mail-GS2 RAM Get Storage <	WIFI		2.4Ghz & 5Ghz		
Graphic Processor Octa-Core Mail-652 BMA I BMA I Borage I Budro of I I	ANDROID Processing				
RAM Image: Strange 4GB Strange 32GB 32GB WHI Image: Strange WHI 24, 5.0, 6.0 Blactodh Image: Strange Strange Android Vesion Image: Strange Strange Feature: Strange Strange Strange MAGO Rand Image: Strange <	Processor		Octa-Core with pair of Quadcore A73 & A53 (Each Core 2.28GHz)		
Storge 326B MIT 326B Blatoth Storge Blatoth Storge Android Version Store Fature Store MAGO Mark Store Mark Store Store Mark Store Store Store Store Mark Store Store Mark Store Store Store Store Store Store Store Store Store Store	Graphics Processor	Octa-Core Mali-G52			
Stonge 326B WIF 6(1) Bluetodh 5.0 Android Version 5.0 Fatere 1.0 Kertere K	RAM	4G8			
Buecodh 5.0 Android Version 5.0 Feature: 11.0 Feature: Sectors: MAGO Smart Present Sectors: MAGO Mikteboard GetOrs: MAGO Disheh GetOrs: MAGO Shark Present City Virtual Meeting account can host up to 50 participants) MAGO Disheh City Virtual Meeting account can host up to 50 participants) Power Stappby City Virtual Meeting account can host up to 50 participants) Power Stappty GetOrs: Powe		32GB			
Android Version 11.0 Feature: Image: Image	WIFI	WIFI 2.4, 5.0, 6.0			
Android Version 11.0 Features WIAGO Smart Present MAGO Smart Present	Bluetooth	5.0			
Features Wireless display up to 9, Reverse broadcast up to 10 MAGO Smart Present Embedded MAGO Miteboard Clivitual Meeting account can host up to 50 participants) MAGO Flash Wee Conference Power Supply Power Supply Power Supply On 180 watt Power Supply On 180 watt Power Supply One Supply <td>Android Version</td> <td colspan="3"></td>	Android Version				
MAGO Whiteboard Embedded MAGO Plash (deo Cherence Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Cl Virtual Meeting account can bast up to 50 participants) Power Supply Mass 1280 (L M L W W) Mass 200 (L M L W W) Weight (kg) Adoos type (L M L W W) Mass 200 (L M L W W) Weight (kg) Mass 200 (L M L W W) Mass 200 (L M L W W) Mass 200 (L M L W W) Mass 200 (L M L W W) </td <td></td> <td></td> <td></td> <td></td>					
MAGO Mikebaard Embedded MAGO Flash MAGO Crierence CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account can host up to 50 participants) Power Souppi CI Virtual Meeting account c	IMAGO Smart Present		Wireless display up to 9, Reverse broadcast up to 100		
Value Conference Conference Value Conference Value Value </td <td>MAGO Whiteboard</td> <td></td> <td></td> <td></td>	MAGO Whiteboard				
Value Conference Conference Value Conference Value Value </td <td></td> <td></td> <td>(1 Virtual Meeting account can beet up to 50 participants)</td> <td></td>			(1 Virtual Meeting account can beet up to 50 participants)		
ower Supply CL 110-240 50/60H2 ower Consumption 180 watt 450 watt technical	ideo Conference		(1 virtual meeting account can nost up to 50 participalits)		
Non-Water 180 watt 450 watt Mechanical					
Mechanical Procession Process					
Dimensions (W x H x D) mm 1488x912x90 (L x H x W) 1710x1035x90 (L x H x W) 1957x175x90 (L x H x W) Weight (kg) 6 6 66.78 kg Induded in the Box 6 66.78 kg Accessories Pack Power Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket Optional Accessories		180 watt	270 watt	450 watt	
Weight (kg) 40.05kg 68.78kg Induced In the Box Forwar Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket Forwar Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket Optional Accessories Forwar Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket Forwar Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket	Mechanical				
Included In the Box Accessories Pack Power Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket Optional Accessories					
Accessories Pack Power Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket Optional Accessories		40.05kg	54.55kg	68.78kg	
Dptional Accessories	ncluded in the Box				
ISB Guest Dongle			Power Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket		
	Accessories Pack Optional Accessories		Power Cable, Remote Control, 2x Stylus Pen, Wall Mount Bracket		



IMAGO TECHNOLOGIES LLC 17 State Street, 40th Floor,New York, NY 10004, United States of America. sales@imagotechs.com



Authorised Partner